

Wireless network configuration in Windows 7

STEP ONE

1. Connect to WEiTI Register
2. Open IE
3. Input credentials (for mion Server)
4. Input password for WiFi access (min. 8 characters)
5. Log out
6. Close IE
7. Disconnect from WEiTI Register

STEP TWO

8. Network and Sharing Center
9. Manage Wireless Networks
10. Add
11. Manually create network profile
12. Configuration:

Network name: WEiTI
Security Type: WPA2-Enterprise
Encryption Type: AES

1. Uncheck: „Start this connection automatically”
2. Next
3. Change Connection Settings
4. On tab „Security”, in field „Choose network authentication method” choose „Microsoft: Protected EAP (PEAP)”
5. Settings
6. Uncheck: “Validate Server Certificate”
7. Field “Select Authentication Method” should be “Secured password (EAP-MSCHAP v2)”
8. “Enable Fast Reconnection” must be checked
9. Configure
10. Turn off “Automatically use my Windows logon name and password”
11. OK
12. In “WEiTI Wireless Network Properties” → “Advanced Settings”
13. In tab “802.1x settings” turn on “Specify authentication mode” and choose: “User authentication”

STEP THREE

14. Connect to WEiTI
15. Login: <mion login name>@mion, Password: <from WEiTI_Register>
16. Open IE and E N J O Y